


CHGM1C

Steering Wheel Control Interface *for select Holden vehicles*



INSTRUCTION MANUAL

CHGM1C

Holden steering wheel control interface for Holden vehicles without CAN-Bus.

Product Contents


1. Interface
2. Harness
3. Instruction

Application

Aveo - 2002 - 2011
Captiva - 2006>
Holden Captiva - 2008 - 2014
Daewoo Winstorm - 2008 - 2011
(South Korean Models)

Non amplified vehicles

For Vehicles with
Original FujitsuTen head units



Prior to installation


Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Aerpro can not be held responsible for the installation of this product.

If you need assistance setting up or using your Aerpro product now or in the future, call Aerpro Support Australia
TEL: 03 – 8587 8898 FAX: 03 – 8587 8866 Mon-Fri 9am – 5pm AEST. If you would like to download a digital copy of this manual, or other Aerpro manuals/software, please visit the <http://aerpro.com> website.

FITTING GUIDE

1. Remove and disconnect the original head unit.
2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.



3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit. This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important Note: This step must be completed before connecting power to the interface. Failure to do so may result in no steering wheel control function.




4. Connect the 14 way molex connector to the interface.



FITTING GUIDE

5. Connect the male power/speaker ISOharnessto the female power/speaker ISOharness from the aftermarket head unit.




For aftermarket head units which do not have an ISO connector the interface uses the following wiring colours:

Wire Colour	Function
Yellow	Permanent 12V
Black	Ground
Red	12V Ignition
Orange	Illumination
Blue	Antenna Remote

Wire Colour	Function
Purple	Right Rear Speaker +
Purple/Black	Right Rear Speaker -
Green	Left Rear Speaker +
Green/Black	Left Rear Speaker -
Grey	Right Front Speaker +
Grey/Black	Right Front Speaker -
White	Left Front Speaker +
White/Black	Left Front Speaker -

6. Connect the female vehicle specific connector to the male vehicle connector. Test head unit for correct operation.



STEERING WHEEL CONTROL FUNCTIONS

